Product information

Dual Clutch Transmission Oil 8100



Description

Superb high-performance oil based on HC-Synthesis oils. The use of an excellent additive combination with extremely shear-resistant viscosity index improvers, modern wear protection additives as well as stable friction agents achieves an excellent coupling performance. This hi-tech lubricant was developed specifically for the requirements of the increasingly prevalent dual clutch transmissions (DCT). Dual clutch transmission oil 8100 is especially also suited for dual clutch transmissions equipped with a shared oil supply for clutch, synchronisation, gear set and hydraulic control.



- optimum stability to aging
- excellent wear resistance
- outstanding resistance to oxidation
- very good low-temperature properties
- excellent shear stability
- excellent viscosity/temperature properties

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

BMW 83 22 0 440 214 • BMW 83 22 2 147 477 • BMW 83 22 2 148 578 • BMW 83 22 2 148 579 • BMW 83 22 2 167 666 • BMW DCTF-1 • BMW MTF LT-5 • Chrysler • Ford WSS-M2C 936-A • Jaguar / Land Rover GX73-M1R564-AA • MB 236.21 • MB 236.24 • Mitsubishi MZ320065 Dia-Queen SSTF-I • Nissan WSS-M2C 936-A • Peugeot Citroen (PSA) 9734.S2 • Porsche 999.917.080.00 • Volvo 1161838 • Volvo 1161839 • VW G 052 182 • VW G 052 529 • VW G 055 529 • ZF TE-ML 11

Technical data

Density at 15 °C 0,845 g/cm³ DIN 51757

Viscosity at 40 °C 33,0 mm²/s ASTM D 7042-04

Viscosity at 100 °C 6,85 mm²/s

ASTM D 7042-04

Viscosity at -40 °C <20000 mPas

DIN 51398

Viscosity index 174

DIN ISO 2909

Pour point -48 °C

DIN ISO 3016

Flash point 200 °C

DIN ISO 2592

DUAL CLUTCH GEAR OIL WILL SECTION SERVING MATERIAL CLUTCH SERVING SERVING MATERIAL CLUTCH SERVING SERVING MATERIAL CLUTCH SERVING SERV

Technical data

Color / appearance gelblich

Areas of application

Recommended for all types of dual-clutch gearbox, which require a special DCT-oil.

Application

The specifications and regulations of the unit or vehicle manufacturers must be observed. The optimal effectiveness is achieved only when used unmixed.

Available pack sizes

1 l Can plastic 3640

D-GB-I-E-P

1 l Can plastic 1180

D-NL-F-GR-ARAB

1 l Can plastic 20466

D-PL-H-RO-TR

5 l Canister plastic 20626

D-GB-I-E-P

20 l Canister plastic 3641

D-GB-I-E-P

1 l Can plastic 21255

ALGERIEN-GB-ARAB-F

60 l Drum sheet metal 3642

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Service-hotline: 0800/8323230
Technical hotline: +49 (0)731/1420-871

www.liqui-moly.de